

THE STOCKMAN 4000 RIDE-ON RANGE



Twin 38" (960mm) Deck - Our Stockman 38" twin blade deck is fabricated, not pressed and is ideal for larger lawn areas where smooth, broad mown swathes are required.



Choice of Transmissions - Cox Live Drive - Our famous toe/heel, forward/ reverse direct transmission. Easy maintenance, minimal moving parts, or
Tuff Torq Hydrostatic Transaxle - Smooth and silent, with inbuilt differential.
Pivoting Front Axle - Reduces chassis stress and 'scalping' over uneven ground.
Commanding forward vision - The riders' eye view. Comfortable, adjustable seating, ergonomically placed controls and clear sight of the terrain ahead.

Laser 'Cut and Keyed' unitary chassis - Precise alignment of components delivers maximum durability.
Straight Line, 'B Section' Drive Belts - Direct, positive power, reduced wear and easy DIY replacement.
Industrial Grade Polypropylene Body Panels - Can't rust, resists scratches and minor dings. Complete with drink holder and tool space.

STYLE. PERFORMANCE.
DEPENDABILITY.

PROUDLY MADE IN AUSTRALIA.

OVER 8 MODELS TO CHOOSE FROM.

YOUR CHOICE OF COX LIVE DRIVE OR

HYDROSTATIC TRANSMISSION.

CHOICE OF ENGINES - HONDA OR BRIGGS & STRATTON.

YOUR CHOICE OF DECK SIZE - 32" OR 38".

For well over 50 years, Cox has been the benchmark against which all other Australian ride-on mowers are judged. Sheer toughness, reliability, performance and value have now reached their zenith with the Cox Stockman 4000 Range.

A proven, time tested engineering and mechanical design has now evolved into the most complete range of ride-on mowers available today, with a configuration of power and deck capacity to suit virtually every small to medium acreage, from the most pristine of lawns, to the rough and tumble of the back paddock.



COX STOCKMAN 4000 LIVE DRIVE MODELS - SPECIFICATIONS

PRODUCT CODE	CS4L15B32	CS4L15B38	CS4L16H32	CS4L17B32	CS4L17B38
ENGINE	Briggs & Stratton Intek OHV	Briggs & Stratton Intek OHV	Honda GXV 530 OHV	Briggs & Stratton Intek OHV	Briggs & Stratton Intek OHV
CYLINDERS	Single Cast Iron Sleeve	Single Cast Iron Sleeve	V-Twin with Cast Iron Sleeve	Single Cast Iron Sleeve	Single Cast Iron Sleeve
POWER*	15.5 HP (11.6 kW, 500cc)	15.5 HP (11.6 kW, 500cc)	16 HP (11.9 kW, 530cc)	17.5 HP (13kW, 500cc)	17.5 HP (13kW, 500cc)
COOLING	Forced Air	Forced Air	Forced Air	Forced Air	Forced Air
IGNITION	Magneton ® Electronic	Magneton ® Electronic	Transistorised Magneto	Magneton ® Electronic	Magneton ® Electronic
LUBRICATION	Splash	Splash	Spin on oil filter, pressure + splash	Spin on oil filter, full pressure	Spin on oil filter, full pressure
AIR CLEANER	Dual Element	Dual Element	Dual Element	Dual Element	Dual Element
FUEL TYPE	Unleaded	Unleaded	Unleaded	Unleaded	Unleaded
CAPACITY	5 Litre	5 Litre	5 Litre	5 Litre	5 Litre
STARTING	12V Key	12V Key	12V Key	12V Key	12V Key
ALTERNATOR	3 Amp	3 Amp	9 Amp	9 Amp	9 Amp
BATTERY	320 CCA	320 CCA	320 CCA	320 CCA	320 CCA
SAFETY SWITCH	Seat & Cutter	Seat & Cutter	Seat & Cutter	Seat & Cutter	Seat & Cutter
FRONT TYRES	13x5.00 -6	13x5.00 -6	13x5.00 -6	13x5.00 -6	13x5.00 -6
REAR TYRES	16x6.50-8	16x6.50-8	16x6.50-8	16x6.50-8	16x6.50-8
CUTTER	32" (805mm) Side Discharge Fabricated Deck	38" (960mm) Side Discharge Fabricated Deck	32" (805mm) Side Discharge Fabricated Deck	32" (805mm) Side Discharge Fabricated Deck	38" (960mm) Side Discharge Fabricated Deck
BLADES	Disc & Heavy Duty Swing Back Blades	2 x Discs & Heavy Duty Swing Back Blades	Disc & Heavy Duty Swing Back Blades	Disc & Heavy Duty Swing Back Blades	2 x Discs & Heavy Duty Swing Back Blades
TRANSMISSION	Cox Toe/heel Friction Live Drive	Cox Toe/heel Friction Live Drive	Cox Toe/heel Friction Live Drive	Cox Toe/heel Friction Live Drive	Cox Toe/heel Friction Live Drive
DIMENSIONS	L 164cm x W 103cm Deflector Down	L 164cm x W 124cm Deflector Down	L 164cm x W 103cm Deflector Down	L 164cm x W 103cm Deflector Down	L 164cm x W 124cm Deflector Down
PRICE	\$	\$	\$	\$	\$

COX STOCKMAN 4000 HYDROSTATIC DRIVE MODELS - SPECIFICATIONS

PRODUCT CODE	CS4H16H32	CS4H17B32	CS4H17B38
ENGINE	Honda GXV 530 OHV	Briggs & Stratton Intek OHV	Briggs & Stratton Intek OHV
CYLINDERS	V-Twin with Cast Iron Sleeve	Single Cast Iron Sleeve	Single Cast Iron Sleeve
POWER*	16 HP (11.9 kW, 530cc)	17.5 HP (13kW, 500cc)	17.5 HP (13kW, 500cc)
COOLING	Forced Air	Forced Air	Forced Air
IGNITION	Transistorised Magneto	Magneton ® Electronic	Magneton ® Electronic
LUBRICATION	Spin on oil filter, pressure + splash	Spin on oil filter, full pressure	Spin on oil filter, full pressure
AIR CLEANER	Dual Element	Dual Element	Dual Element
FUEL TYPE	Unleaded	Unleaded	Unleaded
CAPACITY	5 Litre	5 Litre	5 Litre
STARTING	12V Key	12V Key	12V Key
ALTERNATOR	12 Amp	9 Amp	9 Amp
BATTERY	320 CCA	320 CCA	320 CCA
SAFETY SWITCH	Seat & Cutter	Seat & Cutter	Seat & Cutter
FRONT TYRES	13x5.00 -6	13x5.00 -6	13x5.00 -6
REAR TYRES	16x6.50-8	16x6.50-8	16x6.50-8
CUTTER	32" (805mm) Side Discharge Fabricated Deck	32" (805mm) Side Discharge Fabricated Deck	38" (960mm) Side Discharge Fabricated Deck
BLADES	Disc & Heavy Duty Swing Back Blades	Disc & Heavy Duty Swing Back Blades	2 x Discs & Heavy Duty Swing Back Blades
TRANSMISSION	Tuff Torq K46 Hydrostatic Transaxle with Differential	Tuff Torq K46 Hydrostatic Transaxle with Differential	Tuff Torq K46 Hydrostatic Transaxle with Differential
DIMENSIONS	L 169cm x W 103cm Deflector Down	L 169cm x W 103cm Deflector Down	L 169cm x W 124cm Deflector Down
PRICE	\$	\$	\$

* POWER = GROSS HORSEPOWER @ 3600RPM PER SAE J1995



COX STOCKMAN 4000 RIDE-ON RANGE IS AVAILABLE ONLY FROM COX AUTHORISED, SERVICING DEALERS. SEE OUR WEBSITE FOR YOUR NEAREST.

FREECALL 1800 330 444 | **www.coxmowers.com.au**

70 Landseer Street, Acacia Ridge, Brisbane, Qld 4110

P 07 3323 2222 | F 07 3344 6233

E sales@cox-mowers.com.au

